



## F18

### Product Description

F18 is an innovative biometric fingerprint reader for access control applications, offering unparalleled performance using an advanced algorithm for reliability, precision and excellent matching speed. The F18 features the fastest commercial-based fingerprint matching algorithm and ZK high-performance, high-image quality optical fingerprint sensor. The device offers the flexibility to be installed standalone or with any third party panel that supports 26-bit Wiegand. All the operation can be done on the TFT-LCD. The fingerprint image will display on the screen. That will guide the user to put the finger on to proper position and increase the recognition rate.

TCP/IP and RS485 are available that the device can be used in different network.

#### Standard function



#### Optional function



## Features

- ✓ Fingerprint reader with durable and highly accurate ZK optical sensor
- ✓ 1 touch a-second user recognition
- ✓ Stores 1,500 templates, 5,000 cards and 30,000 transactions
- ✓ Reads Fingerprint and/or Card
- ✓ Optional integrated smart card reader
- ✓ Built-in Serial and Ethernet ports
- ✓ Tamper-proofs switch and alarm outputs
- ✓ Request-to-exit and alarm contacts
- ✓ Audio-Visual indications for acceptance and rejection of valid/invalid fingers



## Specifications

### Capacity

Fingerprint Capacity	1.500 Templates
Card Capacity	5.000
Transaction Capacity	30.000

### Hardware

Platform	ZEM510
Sensor	ZK Optical Sensor
Access Control Interface	Electric Lock, Door Sensor, Exit Button, Alarm, Door Bell

### Display

Display	TFT LCD Screen
---------	----------------

### Environment

Oper. Temp	0°-45°C
Oper. Humidity	20%-80%

### Power

Power	12V, DC 3A
-------	------------

### Communication

Comm. Port	TCP/IP, RS232-485, USB Host
Wiegand	Input & Output
Webserver	Ver. 3.0

### Fingerprint Algorithm

Type	ZK Finger v10.0
Identification	<= 2 seconds
Verification	< 1second
FRR	< 1%
FAR	<= 0.0001%

### Dimensions

Dimensions	180x76x44mm (L x W x D)
Weight	0.26kg

### Firmware

O.S	Linux
Applications	TAC
SDK	Standard SDK

## Connectivity diagram

